



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
16000	10	0.4724	26	1.1024	7	0.2775	4.6	2	28000	32000	0.016
16001	12	0.4724	28	1.1024	7	0.2775	5.1	2.4	26000	30000	0.019
16002	15	0.5906	32	1.2598	8	0.3150	5.6	2.8	22000	26000	0.025
16003	17	0.6693	35	1.3780	8	0.3150	6.8	3.35	20000	24000	0.032
16004	20	0.7874	42	1.6535	8	0.3150	7.9	4.5	18000	21000	0.051
16005	25	0.9843	47	1.8504	8	0.3150	8.35	5.1	15000	18000	0.059
16006	30	1.1811	55	2.1645	9	0.3543	11.2	7.4	13000	15000	0.091
16007	35	1.3779	62	2.4409	9	0.3543	11.7	8.2	12000	14000	0.107
16008	40	1.5748	68	2.6772	9	0.3543	12.6	9.65	10000	12000	0.125
16009	45	1.7716	75	2.9528	10	0.3937	12.9	10.5	9200	11000	0.171
16010	50	1.9650	80	3.1496	10	0.3937	13.2	11.3	8400	9800	0.18
16011	55	2.1653	90	3.5433	11	0.4330	18.6	15.3	7700	9000	0.258
16012	60	2.3620	95	3.7400	11	0.4330	20	17.5	7000	8300	0.283
16013	65	2.5590	100	3.9370	11	0.4330	20.5	18.7	6500	7700	0.307
16014	70	2.7559	110	4.3307	13	0.5118	24.4	22.6	6100	7100	0.441
16015	75	2.9528	115	4.5276	13	0.5118	25	24	5700	6700	0.464
16016	80	3.1496	125	4.9213	14	0.5512	25.4	25.1	5300	6200	0.597
16017	85	3.3465	130	5.1181	14	0.5512	25.9	26.2	5000	5900	0.626
16018	90	3.5433	140	5.5118	16	0.6299	33.5	33.5	4700	5600	0.848
16019	95	3.7402	145	5.7087	16	0.6299	34.5	35	4500	5300	0.885
16020	100	3.9370	150	5.9055	16	0.6299	35	36.5	4200	5000	0.91
16021	105	4.1339	160	6.2992	18	0.7087	43.5	44.5	3800	4700	1.2
16022	110	4.3307	170	6.6929	19	0.7480	53.1	54.1	3600	4500	1.42
16024	120	4.7244	180	7.0866	19	0.7480	54.2	57	3200	4000	1.8
16026	130	5.1181	200	7.8740	22	0.8661	61.8	67	3000	3800	2.63
16028	140	5.5118	210	8.2677	22	0.8661	63	69.8	2600	3400	3.08
16030	150	5.9055	225	8.8583	24	0.9449	74.2	82.5	2400	3200	3.58
16032	160	6.2992	240	9.4488	25	0.9843	88.9	99.8	2200	3000	4.32
16034	170	6.6929	260	10.2362	28	1.1024	100	112	2100	2800	5.77
16036	180	7.0866	280	11.0236	31	1.2205	118	132	2000	2600	7.6
16038	190	7.4803	290	11.4173	31	1.2205	120	140	1900	2400	7.89