



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
6000	10	0.3937	26	1.0236	8	0.315	4.55	1.95	29000	34000	0.019
6001	12	0.4724	28	1.1024	8	0.315	5.1	2.39	26000	30000	0.022
6002	15	0.5906	32	1.2598	9	0.3543	5.6	2.84	22000	26000	0.03
6003	17	0.6693	35	1.378	10	0.3937	6.8	3.35	20000	24000	0.039
6004	20	0.7874	42	1.6535	12	0.4724	9.4	5.05	18000	21000	0.069
6005	25	0.9843	47	1.8504	12	0.4724	10.1	5.85	15000	18000	0.08
6006	30	1.1811	55	2.1645	13	0.5118	13.2	8.3	13000	15000	0.12
6007	35	1.3779	62	2.4409	14	0.5512	16	10.3	12000	14000	0.16
6008	40	1.5748	68	2.6772	15	0.5906	16.8	11.5	10000	12000	0.19
6009	45	1.7716	75	2.9528	16	0.6299	21	15.1	9200	11000	0.25
6010	50	1.965	80	3.1496	16	0.6299	21.8	16.6	8400	9800	0.26
6011	55	2.1653	90	3.5433	18	0.7087	28.3	21.2	7700	9000	0.39
6012	60	2.362	95	3.74	18	0.7087	29.5	23.2	7000	8300	0.42
6013	65	2.559	100	3.937	18	0.7087	30.5	25.2	6500	7700	0.44
6014	70	2.7559	110	4.3307	20	0.7874	38	31	6100	7100	0.6
6015	75	2.9528	115	4.5276	20	0.7874	39.5	33.5	5700	6700	0.64
6016	80	3.1496	125	4.9213	22	0.8661	47.5	40	5300	6200	0.85
6017	85	3.3465	130	5.1181	22	0.8661	49.5	43	5000	5900	0.89
6018	90	3.5433	140	5.5118	24	0.9449	58	49.5	4700	5600	1.15
6019	95	3.7402	145	5.7087	24	0.9449	60.5	54	4500	5300	1.2
6020	100	3.937	150	5.9055	24	0.9449	60	54	4200	5000	1.25
6021	105	4.1399	160	6.2992	26	1.0236	72.1	63.5	3700	4600	1.59
6022	110	4.3307	170	6.6929	28	1.1024	85.2	73.5	3500	4500	1.96
6024	120	4.7244	180	7.0866	28	1.1024	88.4	80	3000	3800	2.07
6026	130	5.1181	200	7.874	33	1.2992	111.9	99.8	2800	3600	3.16
6028	140	5.5118	210	8.2677	33	1.2992	116	108	2400	3200	3.25
6030	150	5.9055	225	8.8583	35	1.3780	132	125	2200	3000	3.98
6032	160	6.2992	240	9.4488	38	1.4961	145	138	2000	2800	4.89
6034	170	6.6929	260	10.2362	42	1.6535	170	170	1900	2600	6.57
6036	180	7.0866	280	11.0236	46	1.8110	188	198	1800	2400	8.58
6038	190	7.4803	290	11.4173	46	1.8110	188	200	1700	2200	8.96
6040	200	7.8740	310	12.2047	51	2.0079	205	225	1600	2000	11.71
6044	220	8.6614	340	13.3858	56	2.2047	252	268	1400	1800	18.07
6048	240	9.4488	360	14.1732	56	2.2047	270	292	1200	1600	20.08
6052	260	10.2362	400	15.7480	65	2.5591	292	372	1100	1500	28.9
6056	280	11.0236	420	16.5354	65	2.5591	305	408	950	1300	32.3
6064	320	12.5984	480	18.8976	74	2.9134	345	510	900	1100	48.6
6072	360	14.1732	540	21.2598	82	3.2283	400	622	750	950	68.3
6080	400	15.7480	600	23.6220	90	3.5433	512	868	630	800	89.7