



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
6200	10	0.3973	30	1.1811	9	0.3543	5.1	2.39	25000	30000	0.032
6201	12	0.4724	32	1.2598	10	0.3937	6.1	2.75	22000	26000	0.037
6202	15	0.5906	35	1.3779	11	0.4331	7.75	3.6	19000	23000	0.045
6203	17	0.6693	40	1.5748	12	0.4724	9.6	4.6	18000	21000	0.065
6204	20	0.7874	47	1.8504	14	0.5512	12.8	6.65	16000	18000	0.11
6205	25	0.9843	52	2.0472	15	0.5906	14	7.85	13000	15000	0.13
6206	30	1.1811	62	2.4409	16	0.6299	19.5	11.3	11000	13000	0.2
6207	35	1.3779	72	2.8346	17	0.6693	25.7	15.3	9800	11000	0.29
6208	40	1.5748	80	3.1496	18	0.7087	29.1	17.8	8700	10000	0.37
6209	45	1.7716	85	3.3465	19	0.748	32.5	20.4	7800	9200	0.41
6210	50	1.965	90	3.5433	20	0.7841	35	23.2	7100	8300	0.46
6211	55	2.1653	100	3.937	21	0.8268	43.5	29.2	6400	7600	0.61
6212	60	2.362	110	4.3307	22	0.8661	52.5	36	6000	7000	0.78
6213	65	2.559	120	4.7244	23	0.9055	57.5	40	5500	6500	0.99
6214	70	2.7559	125	4.9213	24	0.9449	62	44	5100	6000	1.05
6215	75	2.9528	130	5.1181	25	0.9843	66	49.5	4800	5600	1.2
6216	80	3.1496	140	5.7087	26	1.0236	72.5	53	4500	5300	1.4
6217	85	3.3465	150	5.9055	28	1.1024	83.5	64	4200	5000	1.8
6218	90	3.5433	160	6.2992	30	1.1811	96	71.5	4000	4700	2.15
6219	95	3.7402	170	6.6929	32	1.2598	109	82	3700	4400	2.6
6220	100	3.9370	180	7.0866	34	1.3386	122	93	3500	4200	3.15
6221	105	4.1339	190	7.4803	36	1.4173	146	105	3400	4000	3.7
6222	110	4.3307	200	7.8740	38	1.4961	151	118	3200	3800	4.4
6224	120	4.7244	215	8.4646	40	1.5748	157	131	2600	3400	5.3
6226	130	5.1181	230	9.0551	40	1.5748	165	148	2400	3200	6.2
6228	140	5.5118	250	9.8425	42	1.6535	179	167	2100	2900	7.8
6230	150	5.9055	270	10.6299	45	1.7717	205	200	2000	2700	9.8
6232	160	6.2992	290	11.4173	48	1.8898	215	218	1900	2500	12.3
6234	170	6.6929	310	12.2047	52	2.0472	250	265	1700	2200	15.3
6236	180	7.0866	320	12.5984	52	2.0472	262	285	1600	2000	15.7
6238	190	7.4803	340	13.3858	55	2.1654	285	322	1500	1900	18.8
6240	200	7.8740	360	14.1732	58	2.2835	288	332	1400	1800	22.6
6244	220	8.6614	400	15.7480	65	2.5591	355	365	1200	1600	36.5
6248	240	9.4488	440	17.3228	72	2.8346	358	467	1000	1400	53.9