



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
62200	10	0.3937	30	1.1811	14	0.5512	5.1	2.39	25000	30000	0.04
62201	12	0.4724	32	1.2598	14	0.5512	6.1	2.75	22000	26000	0.045
62202	15	0.5906	35	1.378	14	0.5512	7.75	3.6	19000	23000	0.054
62203	17	0.6693	40	1.5748	16	0.6299	9.6	4.6	18000	21000	0.083
62204	20	0.7874	47	1.8504	18	0.7086	12.8	6.65	16000	18000	0.13
62205	25	0.9843	52	2.1645	18	0.7086	14	7.85	13000	15000	0.15
62206	30	1.1811	62	2.4409	20	0.7874	19.5	11.3	11000	13000	0.24
62207	35	1.3779	72	2.8346	23	0.9055	25.7	15.3	9800	11000	0.37
62208	40	1.5748	80	3.1496	23	0.9055	29.1	17.8	8700	10000	0.44
62209	45	1.7716	85	3.3464	23	0.9055	32.5	20.4	7800	9200	0.48
62210	50	1.965	90	3.5464	23	0.9055	35	23.2	7100	8300	0.52
62211	55	2.1653	100	3.9370	25	0.9843	43.5	29.2	6400	7600	0.7
62212	60	2.3620	110	4.3307	28	1.1024	52.5	36	6000	7000	0.97
62213	65	2.5590	120	4.7244	31	1.2205	57.5	40	5500	6500	1.25
62214	70	2.7559	125	4.9213	31	1.2205	62	44	5100	6000	1.3
62215	75	2.9528	130	5.1181	31	1.2205	66	49.5	4800	5600	1.39
62216	80	3.1496	140	5.7087	33	1.2992	72.5	53	4500	5300	1.9
62217	85	3.3465	150	5.9055	36	1.4173	83.5	64	4200	5000	2.6
62218	90	3.5433	160	6.2992	40	1.5748	96	71.5	4000	4700	2.9
62219	95	3.7402	170	6.6929	43	1.6929	109	82	3700	4400	3.3
62220	100	3.9370	180	7.0866	46	1.8110	122	93	3500	4200	3.6