



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
62300	10	0.3937	35	1.378	17	0.6693	8.2	3.5	23000	27000	0.073
62301	12	0.4724	37	1.4567	17	0.6693	9.7	4.2	20000	24000	0.0814
62302	15	0.5906	42	1.6535	17	0.6693	11.4	5.45	17000	21000	0.105
62303	17	0.6693	47	1.8504	19	0.748	13.5	6.55	16000	19000	0.146
62304	20	0.7874	52	2.0447	21	0.8276	15.9	7.9	14000	17000	0.195
62305	25	0.9843	62	2.4409	24	0.9448	21.2	10.9	12000	14000	0.306
62306	30	1.1811	72	2.8346	27	1.063	26.7	15	10000	12000	0.478
62307	35	1.3779	80	3.1496	31	1.2204	33.5	19.1	8800	10000	0.647
62308	40	1.5748	90	3.5433	33	1.2992	40.5	24	7800	9200	0.885
62309	45	1.7716	100	3.937	36	1.4173	53	32	7000	8200	1.156
62310	50	1.9685	110	4.3307	40	1.5748	62	38.5	6400	7500	1.498
62311	55	2.1654	120	4.7244	43	1.6929	71.5	45	5800	6800	1.918
62312	60	2.3622	130	5.1181	46	1.8110	82	52	5400	6300	2.3
62313	65	2.5590	140	5.7087	48	1.8898	92.5	60	4900	5800	2.7
62314	70	2.7559	150	5.9055	51	2.0078	104	68	4600	5400	3.2
62315	75	2.9528	160	6.2992	55	2.1654	113	77	4300	5000	3.7
62316	80	3.1496	170	6.6929	58	2.2835	123	86.5	4000	4700	4.3
62317	85	3.3465	180	7.0866	60	2.3620	133	97	3800	4500	4.95
62318	90	3.5433	190	7.1803	64	2.5197	143	107	3600	4200	5.6
62319	95	3.7402	200	7.8740	67	2.6378	153	119	3300	3900	7.6