



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
6300	10	0.3937	35	1.3779	11	0.4331	8.2	3.5	23000	27000	0.053
6301	12	0.4724	37	1.4567	12	0.4724	9.7	4.2	20000	24000	0.06
6302	15	0.5906	42	1.6535	13	0.5118	11.4	5.45	17000	21000	0.082
6303	17	0.6693	47	1.8504	14	0.5512	13.5	6.55	16000	19000	0.12
6304	20	0.7874	52	2.0472	15	0.5906	15.9	7.9	14000	17000	0.14
6305	25	0.9843	62	2.4409	17	0.6693	21.2	10.9	12000	14000	0.23
6306	30	1.1811	72	2.8346	19	0.748	26.7	15	10000	12000	0.35
6307	35	1.3779	80	3.1496	21	0.8268	33.5	19.1	8800	10000	0.46
6308	40	1.5748	90	3.5433	23	0.9055	40.5	24	7800	9200	0.63
6309	45	1.7716	100	3.937	25	0.9843	53	32	7000	8200	0.83
6310	50	1.965	110	4.3307	27	1.063	62	38.5	6400	7500	1.05
6311	55	2.1653	120	4.7244	29	1.1417	71.5	45	5800	6800	1.35
6312	60	2.362	130	5.1181	31	1.2205	82	52	5400	6300	1.7
6313	65	2.559	140	5.7087	33	1.2992	92.5	60	4900	5800	2.1
6314	70	2.7559	150	5.9055	35	1.378	104	68	4600	5400	2.5
6315	75	2.9528	160	6.2992	37	1.4567	113	77	4300	5000	3
6316	80	3.1496	170	6.6929	39	1.5354	123	86.5	4000	4700	3.6
6317	85	3.3465	180	7.0866	41	1.6142	133	97	3800	4500	4.25
6318	90	3.5433	190	7.4803	43	1.6929	143	107	3600	4200	4.9
6319	95	3.7402	200	7.874	45	1.7717	153	119	3300	3900	5.65
6320	100	3.9370	215	8.2677	47	1.8504	173	141	3200	3700	7
6321	105	4.1339	225	8.8583	49	1.9291	184	153	2600	3200	8.1
6322	110	4.3307	240	9.4488	50	1.9685	205	178	2400	3000	9.55
6324	120	4.7244	260	10.2362	55	2.1654	228	208	2200	2800	12.2
6326	130	5.1181	280	11.0236	58	2.2835	253	242	2000	2600	14.8
6328	140	5.5118	300	11.8110	62	2.4409	275	272	1900	2400	18.33
6330	150	5.9055	320	12.5984	65	2.5591	288	295	1700	2200	21.9
6332	160	6.2992	340	13.3858	68	2.6772	313	340	1600	2000	26.43
6334	170	6.6929	360	14.1732	72	2.8346	335	378	1500	1900	31.14