



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
63000	10	0.3937	26	1.0236	12	0.4724	4.58	1.98	26000	30000	0.025
63001	12	0.4724	28	1.1024	12	0.4724	5.1	2.39	26000	30000	0.029
63002	15	0.5906	32	1.2598	13	0.5118	5.6	2.84	22000	26000	0.04
63003	17	0.6693	35	1.3780	14	0.5512	6.8	3.35	20000	24000	0.052
63004	20	0.7874	42	1.6535	16	0.6299	9.4	5.05	18000	21000	0.088
63005	25	0.9843	47	1.8504	16	0.6299	10.1	5.58	15000	18000	0.1
63006	30	1.1811	55	2.1654	19	0.7480	13.2	8.3	13000	15000	0.16
63007	35	1.3780	62	2.4409	20	0.7874	16	10.3	12000	14000	0.21
63008	40	1.5748	68	2.6772	21	0.8268	16.8	11.5	10000	12000	0.26
63009	45	1.7717	75	2.9528	23	0.9055	20.8	14.6	5600	6600	0.34
63010	50	1.9685	80	3.1496	23	0.9055	21.6	16	5000	6000	0.37

