



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
6700	10	0.3937	15	0.5906	3	0.1181	0.80	0.39	26000	34000	0.002
6701	12	0.4724	18	0.7087	4	0.1575	0.91	0.53	22000	30000	0.004
6702	15	0.5906	21	0.8268	4	0.1575	0.85	0.49	20000	28000	0.005
6703	17	0.6693	23	0.9055	4	0.1575	0.96	0.61	18000	26000	0.006
6704	20	0.7874	27	1.0630	4	0.1575	1.03	0.72	16000	22000	0.01
6705	25	0.9843	32	1.2598	4	0.1575	1.09	0.83	14000	18000	0.015
6706	30	1.1811	37	1.4567	4	0.1575	1.17	0.98	11000	15000	0.018
6707	35	1.3780	44	1.7323	5	0.1969	1.85	1.63	9000	13000	0.02
6708	40	1.5748	50	1.9685	6	0.2362	2.52	2.23	8000	12000	0.023
6709	45	1.7717	55	2.1654	6	0.2362	2.57	2.40	7000	11000	0.025
6710	50	1.9685	62	2.4409	6	0.2362	2.66	2.63	6000	9000	0.034
6711	55	2.1654	68	2.6772	7	0.2756	2.88	3.07	5000	8000	0.055

bearings  
box