



Model	Inner Dimension		Outer Dimension		Width		Basic Load Ratings		Limiting Speeds		Weight
	d		D		B		Dynamic	Static	Grease	Oil	Approx.
	mm	inch	mm	inch	mm	inch	Cr(KN)	Cor(KN)	rpm	rpm	kg
6800	10	0.3937	19	0.748	5	0.1969	1.59	0.75	28000	36000	0.005
6801	12	0.4724	21	0.8268	5	0.1969	1.91	1.04	24000	32000	0.006
6802	15	0.5906	24	0.9449	5	0.1969	2.07	1.25	22000	30000	0.007
6803	17	0.6693	26	1.0236	5	0.1969	2.13	1.36	20000	28000	0.008
6804	20	0.7874	32	1.2598	7	0.2756	3.48	2.23	18000	24000	0.009
6805	25	0.9843	37	1.4567	7	0.2756	3.68	2.63	16000	20000	0.022
6806	30	1.1811	42	1.6535	7	0.2756	4	3.15	13000	17000	0.026
6807	35	1.378	47	1.8504	7	0.2756	4.27	3.6	11000	15000	0.029
6808	40	1.5748	52	2.0472	7	0.2756	4.41	3.89	10000	13000	0.033
6809	45	1.7716	58	2.2834	7	0.2756	4.59	4.33	9000	12000	0.04
6810	50	1.9685	65	2.559	7	0.2756	6.61	6.08	8500	10000	0.052
6811	55	2.1654	72	2.8346	9	0.3543	8.53	8.08	8000	9500	0.083
6812	60	2.3622	78	3.0709	10	0.3937	9.2	8.76	7000	8500	0.106
6813	65	2.5591	85	3.3465	10	0.3937	10.51	9.42	6700	8000	0.125
6814	70	2.7559	90	3.5433	10	0.3937	10.89	10.09	6300	7500	0.135
6815	75	2.9528	95	3.7402	10	0.3937	11.23	10.76	6000	7000	0.145
6816	80	3.1496	100	3.9370	10	0.3937	11.32	11.08	5600	6700	0.155
6817	85	3.3465	110	4.3307	13	0.5118	17.6	18.3	5000	6300	0.27
6818	90	3.5433	115	4.5276	13	0.5118	17.85	18.9	4800	6000	0.28
6819	95	3.7402	120	4.7244	13	0.5118	18.1	19.61	4500	5600	0.3
6820	100	3.9370	125	4.9213	13	0.5118	18.34	20.3	4300	5300	0.315
6821	105	4.1339	130	5.1181	13	0.5118	18.91	20.92	4000	5000	0.325
6822	110	4.3307	140	5.5118	16	0.6299	28.1	30.7	3800	5000	0.51
6824	120	4.7244	150	5.9055	16	0.6299	28.9	32.9	3600	4500	0.55
6826	130	5.1181	165	6.4961	18	0.7087	37.9	42.9	3400	4300	0.795
6828	140	5.5118	175	6.8898	18	0.7087	42.8	48.2	3200	4100	0.85
6830	150	5.9055	190	7.4803	20	0.7874	47.9	55.9	3000	3800	1.16
6832	160	6.2992	200	7.8740	20	0.7874	48.2	59.6	2800	3600	1.25
6834	170	6.6929	215	8.4646	22	0.8661	51.7	62.1	2500	3300	1.82
6836	180	7.0866	225	8.8583	22	0.8661	59	73.5	2100	2900	2.05
6838	190	7.4803	240	9.4488	24	0.9449	62.9	79	2000	2800	2.4
6840	200	7.8740	250	9.8425	24	0.9449	64.5	82	2200	2600	2.6